

AXIAL MACHINE ST 100x3P-4P


DESCRIPTION OF THE MACHINE


THE MACHINE REALIZES SERIES OF PROCESSES SHAPING THE ENDS OF STEEL PIPES AS FLARING, EXPANDING, ETC., USING DEDICATED TOOLING. N°1 RAMMING STATION - N°3 OR 4 OR 6 PASSES.

(WORK DIAMETER Ø100)



FRAME WITH BUILT-IN HYDRAULIC UNIT
PLC FOR MACHINE CONTROL
PUSH-BUTTON PANEL OR PEDAL BOARD FOR CYCLE START
PROGRAMMING KEYBOARD (TOUCH SCREEN)
ELECTRONIC CONTROL OF WORKING QUOTAS
ELECTRICAL CABINET ON BOARD
MAGNETIC OR ELECTROMECHANICAL SAFETY SWITCHES
SAFETY COVERS





TECHNICAL SPECIFICATIONS	
Tension: 400V	MAX calibration lenght: 80mm (dependent thickness / diameter)
Frequency: 50Hz	MAX reduction: 10mm single step
Auxiliar circuits Tension: 24V	MAX enlargment: 10mm single step
Width (mm): 2060 (3P) / 2734 (4P)	Pipe Thickness MAX: 2mm
Lenght (mm): 2367	Power of the upper pad clamp: 38 Ton (each vice)
Height (mm): 2525.5	Max stroke of the pad clamp: 250mm
Weight Kg: 9000 (3P) / 9800 (4P) - (without oil)	Power of the axial punch: 24 Ton (each Axial cylinder)
Work diameter: 30-100 mm	Max stroke of the punch: 250mm
Average machine time (sec): 5/10	Max height available for mounting tool: 432mm
Average set up time (min): 10/15	

OPTIONAL	DESCRIPTION
Hoist	Hoist 200Kg for lifting tools, incorporated in the machine
Remote assistance System	Remote assistance system via internet
Objectivation sensors	Connector for piece presence sensor or special cycles
Laser scanner	Replaces the light curtains
Motorized head	It is possible to insert a motorized head to perform operations such as:
	boring, end milling, chamfering etc.
Trolley	Trolleys on wheels to facilitate the loading / unloading of the equipment
	on the machine
OK / NOK piece control heads	Plug for conformal piece checking during the work cycle